

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

HUECK Hybrid-System-Kleber / hellgrau
HUECK Hybrid-System-Kleber / dunkelgrau
Art.: Z91804700.0001 / Z91808800.0001

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses of the substance or mixture:

Adhesive
Assembly material

Uses advised against:

No information available at present.

1.3 Details of the supplier of the safety data sheet

Eduard Hueck GmbH & Co. KG, Loher Str. 9, D-58511 Lüdenscheid
Telephone: +49 (0) 23 51 151-1, Fax:
info@hueck.de

Manufacturer:

Weiss Chemie + Technik GmbH & Co. KG, Hansastrasse 2, D-35708 Haiger
Phone: +49(0)2773/815-0, Fax:
msds@weiss-chemie.de www.weiss-chemie.de

Qualified person's e-mail address: info@chemical-check.de, k.schnurbusch@chemical-check.de Please DO NOT use for requesting Safety Data Sheets.

1.4 Emergency telephone

Emergency information services / official advisory body:

Telephone number of the company in case of emergencies:

+49 (0) 700 / 24 112 112 (WIC)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

2.1.1 Classification according to Regulation (EC) 1272/2008 (CLP)

Not determined

2.1.2 Classification according to Directives 67/548/EEC and 1999/45/EC (including amendments)

The mixture is not classified as dangerous in the terms of the directive 1999/45/EC.

2.2 Label elements

2.2.1 Labeling according to Regulation (EC) 1272/2008 (CLP)

Not determined

2.2.2 Labeling according to Directives 67/548/EEC and 1999/45/EC (including amendments)

Symbols: Not applicable

Indications of danger: ---

R-phrases:

S-phrases:

Additions:

Safety data sheet available for professional user on request.

2.3 Other hazards

The mixture does not contain any vPvB substance (vPvB = very persistent, very bioaccumulative) or is not included under XIII of the regulation (EC) 1907/2006.
The mixture does not contain any PBT substance (PBT = persistent, bioaccumulative, toxic) or is not included under XIII of the regulation (EC) 1907/2006.

SECTION 3: Composition/information on ingredients

3.1 Substance

n.a.

3.2 Mixture

trimethoxyvinylsilane	
Registration number (REACH)	01-2119513215-52-XXXX
Index	---
EINECS, ELINCS, NLP	220-449-8
CAS	CAS 2768-02-7
content %	1-5
Classification according to Directive 67/548/EEC	Flammable, R10 Harmful, Xn, R20
Classification according to Regulation (EC) 1272/2008 (CLP)	Flam. Liq. 3, H226 Acute Tox. 4, H332
3-(trimethoxysilyl)propylamine	
Registration number (REACH)	---
Index	---
EINECS, ELINCS, NLP	237-511-5
CAS	CAS 13822-56-5
content %	1-<3
Classification according to Directive 67/548/EEC	Irritant, Xi, R38 Irritant, Xi, R41
Classification according to Regulation (EC) 1272/2008 (CLP)	Skin Irrit. 2, H315 Eye Dam. 1, H318

For the text of the R-phrases / H-phrases and classification codes (GHS/CLP), see Section 16.
The substances named in this section are given with their actual, appropriate classification!

For substances that are listed in appendix VI, table 3.1/3.2 of the regulation (EC) no. 1272/2008 (CLP regulation) this means that all notes that may be given here for the named classification have been taken into account.

SECTION 4: First aid measures

4.1 Description of first aid measures

Never pour anything into the mouth of an unconscious person!

Inhalation

Remove person from danger area.

Supply person with fresh air and consult doctor according to symptoms.

Skin contact

Remove polluted, soaked clothing immediately, wash thoroughly with plenty of water and soap, in case of irritation of the skin (flare), consult a doctor.

Unsuitable cleaning product:

Solvent

Thinners

Eye contact

Remove contact lenses.

Wash thoroughly for several minutes using copious water. Seek medical help if necessary.

Ingestion

Rinse the mouth thoroughly with water.

Do not induce vomiting. Consult doctor immediately.

4.2 Most important symptoms and effects, both acute and delayed

If applicable delayed symptoms and effects can be found in section 11 and the absorption route in section 4.1. In certain cases, the symptoms of poisoning may only appear after an extended period / after several hours.

4.3 Indication of any immediate medical attention and special treatment needed

n.c.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

CO2

Extinction powder

Water jet spray

Large fire:

Water jet spray / alcohol resistant foam

Unsuitable extinguishing media

None known

5.2 Special hazards arising from the substance or mixture

In case of fire the following can develop:

Oxides of carbon

Oxides of sulphur

Toxic gases

5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes.

Protective respirator with independent air supply.

According to size of fire

Full protection, if necessary

Dispose of contaminated extinction water according to official regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Ensure sufficient supply of air.

Avoid contact with eyes or skin.

If applicable, caution - risk of slipping

6.2 Environmental precautions

If leakage occurs, dam up.

Resolve leaks if this possible without risk.

Prevent surface and ground-water infiltration, as well as ground penetration.

Prevent from entering drainage system.

If accidental entry into drainage system occurs, inform responsible authorities.

6.3 Methods and material for containment and cleaning up

Soak up with absorbent material (e.g. universal binding agent, sand, diatomaceous earth, sawdust) and dispose of according to Section 13.

Or:

Pick up mechanically and dispose of according to Section 13.

6.4 Reference to other sections

For personal protective equipment see Section 8 and for disposal instructions see Section 13.

SECTION 7: Handling and storage

In addition to information given in this section, relevant information can also be found in section 8 and 6.1.

7.1 Precautions for safe handling

7.1.1 General recommendations

Ensure good ventilation.

Avoid contact with eyes.

Avoid long lasting or intensive contact with skin.

Eating, drinking, smoking, as well as food-storage, is prohibited in work-room.

Observe directions on label and instructions for use.

7.1.2 Notes on general hygiene measures at the workplace

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

7.2 Conditions for safe storage, including any incompatibilities

Store product closed and only in original packing.

Not to be stored in gangways or stair wells.

Store cool

Store in a dry place.

7.3 Specific end use(s)

No information available at present.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

The methanol listed below can arise upon contact with water.

Chemical Name	Calcium carbonate	Content %:
WEL-TWA: 4 mg/m3 (respirable dust), 10 mg/m3 (total inhalable dust)	WEL-STEL: ---	---
BMGV: ---	Other information: ---	
Chemical Name	Methanol	Content %:
WEL-TWA: 200 ppm (266 mg/m3) (WEL), 200 ppm (260 mg/m3) (EU)	WEL-STEL: 250 ppm (333 mg/m3) (WEL)	---
BMGV: ---	Other information: Sk (WEL, EU)	

WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period) EH40. AGW = "Arbeitsplatzgrenzwert" (workplace limit value, Germany). | WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period). | BMGV = Biological monitoring guidance value EH40. BGV = "Biologischer Grenzwert" (biological limit value,

Germany) | Other information: Sen = Capable of causing occupational asthma. Sk = Can be absorbed through skin. Carc = Capable of causing cancer and/or heritable genetic damage.
 ** = The exposure limit for this substance is repealed through the TRGS 900 (Germany) of January 2006 with the goal of revision.

trimethoxyvinylsilane						
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
Workers / employees	Human - dermal	Short term, systemic effects	DNEL	0,69	mg/kg bw/day	
Workers / employees	Human - inhalation	Short term, systemic effects	DNEL	4,9	mg/m3	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	0,69	mg/kg bw/day	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	4,9	mg/kg	
	Environment - freshwater		PNEC	0,34	mg/l	
	Environment - marine		PNEC	0,034	mg/l	
	Environment - water, sporadic (intermittent) release		PNEC	3,4	mg/l	
	Environment - sewage treatment plant		PNEC	110	mg/l	
Consumer	Human - dermal	Short term, systemic effects	DNEL	26,9	mg/kg bw/day	
Consumer	Human - inhalation	Short term, systemic effects	DNEL	93,4	mg/m3	
Consumer	Human - dermal	Long term, systemic effects	DNEL	0,3	mg/kg bw/day	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	1,04	mg/m3	
Consumer	Human - oral	Long term, systemic effects	DNEL	0,3	mg/kg bw/day	
	Environment - sediment, freshwater		PNEC	0,27	mg/kg	
	Environment - sediment, marine		PNEC	0,12	mg/kg	
	Environment - soil		PNEC	0,046	mg/kg	

Calcium carbonate						
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	10	mg/m3	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	10	mg/m3	
Consumer	Human - oral	Short term, systemic effects	DNEL	6,1	mg/kg bw/day	
Consumer	Human - oral	Long term, systemic effects	DNEL	6,1	mg/kg bw/day	
	Environment - sewage treatment plant		PNEC	100	mg/l	

Methanol						
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
Workers / employees	Human - dermal	Short term, systemic effects	DNEL	40	mg/kg body weight/day	
Workers / employees	Human - inhalation	Short term, systemic effects	DNEL	260	mg/m3	
Workers / employees	Human - inhalation	Short term, local effects	DNEL	260	mg/m3	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	40	mg/kg body weight/day	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	260	mg/m3	
Workers / employees	Human - inhalation	Long term, local effects	DNEL	260	mg/m3	
Consumer	Human - dermal	Short term, systemic effects	DNEL	8	mg/kg body weight/day	
Consumer	Human - inhalation	Short term, systemic effects	DNEL	50	mg/m3	
Consumer	Human - oral	Short term, systemic effects	DNEL	8	mg/kg body weight/day	
Consumer	Human - dermal	Long term, systemic effects	DNEL	8	mg/kg body weight/day	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	50	mg/m3	
Consumer	Human - oral	Long term, systemic effects	DNEL	8	mg/kg body weight/day	
	Environment - freshwater		PNEC	154	mg/l	
	Environment - marine		PNEC	154	mg/l	
	Environment - sediment, freshwater		PNEC	570,4	mg/kg	
	Environment - sediment, marine		PNEC	57,04	mg/kg	
	Environment - soil		PNEC	23,54	mg/kg	
	Environment - water, sporadic (intermittent) release		PNEC	1540	mg/l	

Environment - sewage treatment plant		PNEC	100	mg/l	
--------------------------------------	--	------	-----	------	--

8.2 Exposure controls

8.2.1 Appropriate engineering controls

Ensure good ventilation. This can be achieved by local suction or general air extraction. If this is insufficient to maintain the concentration under the WEL or AGW values, suitable breathing protection should be worn.
 Applies only if maximum permissible exposure values are listed here.

8.2.2 Individual protection measures, such as personal protective equipment

General hygiene measures for the handling of chemicals are applicable.
 Wash hands before breaks and at end of work.
 Keep away from food, drink and animal feedingstuffs.
 Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

Eye/face protection:
 Tight fitting protective goggles with side protection (EN 166).

Skin protection - Hand protection:
 Chemical resistant protective gloves (EN 374).
 Recommended
 Protective nitrile gloves (EN 374)
 Minimum layer thickness in mm:
 >= 0,35
 Permeation time (penetration time) in minutes:
 >= 120
 The breakthrough times determined in accordance with EN 374 Part 3 were not obtained under practical conditions.
 The recommended maximum wearing time is 50% of breakthrough time.
 Protective hand cream recommended.

Skin protection - Other:
 Protective working garments (e.g. safety shoes EN ISO 20345, long-sleeved protective working garments)

Respiratory protection:
 Normally not necessary.

Thermal hazards:
 Not applicable

Additional information on hand protection - No tests have been performed.
 In the case of mixtures, the selection has been made according to the knowledge available and the information about the contents.
 Selection of materials derived from glove manufacturer's indications.
 Final selection of glove material must be made taking the breakthrough times, permeation rates and degradation into account.
 Selection of a suitable glove depends not only on the material but also on other quality characteristics and varies from manufacturer to manufacturer.
 In the case of mixtures, the resistance of glove materials cannot be predicted and must therefore be tested before use.
 The exact breakthrough time of the glove material can be requested from the protective glove manufacturer and must be observed.

8.2.3 Environmental exposure controls

No information available at present.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state: Pastelike, Liquid
 Colour: According to specification
 Odour: Characteristic
 Odour threshold: Not determined
 pH-value: Not determined
 Melting point/freezing point: Not determined
 Initial boiling point and boiling range: Not determined
 Flash point: Not determined
 Evaporation rate: n.a.
 Flammability (solid, gas): n.a.
 Lower explosive limit: Not determined
 Upper explosive limit: Not determined
 Vapour pressure: Not determined
 Vapour density (air = 1): Not determined
 Density: -1,6 g/cm3 (20°C)
 Bulk density: Not determined
 Solubility(ies): Not determined
 Water solubility: Insoluble
 Partition coefficient (n-octanol/water): Not determined
 Auto-ignition temperature: n.a.
 Decomposition temperature: Not determined
 Viscosity: Not determined
 Explosive properties: Product is not explosive.
 Oxidising properties: No

9.2 Other information

Miscibility: Not determined
 Fat solubility / solvent: Not determined
 Conductivity: Not determined
 Surface tension: Not determined
 Solvents content: Not determined
 Metal content: Not determined
 Molar mass: Not determined
 Chemical heat of combustion: Not determined

SECTION 10: Stability and reactivity

10.1 Reactivity

The product has not been tested.

10.2 Chemical stability

Stable with proper storage and handling.

10.3 Possibility of hazardous reactions

reacts with water

10.4 Conditions to avoid

See also section 7.

Strong heat

Moisture

10.5 Incompatible materials

See also section 7.

None known

10.6 Hazardous decomposition products

See also section 5.2

In case of contact with water:

Methanol

SECTION 11: Toxicological information

Possibly more information on health effects, see Section 2.1 (classification).

HUECK Hybrid-System-Kleber / hellgrau
 HUECK Hybrid-System-Kleber / dunkelgrau
 Art.: Z91804700.0001 / Z91808800.0001

Toxicity/effect	End point	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:						n.d.a.
Acute toxicity, by dermal route:						n.d.a.
Acute toxicity, by inhalation:	ATE	>20	mg/l /4h			calculated value, Vapours
Skin corrosion/irritation:						n.d.a.
Serious eye damage/irritation:						n.d.a.
Respiratory or skin sensitisation:						n.d.a.
Germ cell mutagenicity:						n.d.a.
Carcinogenicity:						n.d.a.
Reproductive toxicity:						n.d.a.
Specific target organ toxicity - single exposure (STOT-SE):						n.d.a.
Specific target organ toxicity - repeated exposure (STOT-RE):						n.d.a.
Aspiration hazard:						n.d.a.
Respiratory tract irritation:						n.d.a.
Repeated dose toxicity:						n.d.a.
Symptoms:						n.d.a.
Other information:						Classification according to calculation procedure.

trimethoxyvinylsilane						
Toxicity/effect	End point	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	7120	mg/kg	Rat	OECD 401 (Acute Oral Toxicity)	
Acute toxicity, by dermal route:	LD50	3540	mg/kg	Rabbit		
Acute toxicity, by inhalation:	LD50	2773	ppm /4h	Rat	OECD 403 (Acute Inhalation Toxicity)	Aerosol
Acute toxicity, by inhalation:	LC50	16,8	mg/l /4h	Rat		
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute Dermal Irritation/Corrosion)	Slightly irritant
Skin corrosion/irritation:				Rabbit		Not irritant
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Not irritant
Respiratory or skin sensitisation:				Guinea pig	OECD 406 (Skin Sensitisation)	Not sensitizing
Germ cell mutagenicity:						Negative
Carcinogenicity:						Negative
Reproductive toxicity:						Negative
Repeated dose toxicity:	NO AEL	<62,5	mg/kg	Rat	OECD 422 (Combined Repeated Dose Tox. Study with the Reproduction/D. developm. Tox. Screening Test)	
Repeated dose toxicity:	NO AEL	10	mg/l	Rat	OECD 422 (Combined Repeated Dose Tox. Study with the Reproduction/D. developm. Tox. Screening Test)	Vapours
Symptoms:						mucous membrane irritation
Symptoms:						drowsiness, dizziness, nausea, abdominal pain, breathing difficulties, visual disturbances
Symptoms:						mucous membrane irritation

3-(trimethoxysilyl)propylamine						
Toxicity/effect	End point	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>2000	mg/kg	Rat		
Acute toxicity, by dermal route:	LD50	>2000	mg/kg	Rat		
Acute toxicity, by inhalation:						n.d.a.
Skin corrosion/irritation:				Rabbit		Irritant
Serious eye damage/irritation:				Rabbit		Intensively irritant
Respiratory or skin sensitisation:				Guinea pig		No (skin contact)

Germ cell mutagenicity:					OECD 471 (Bacterial Reverse Mutation Test)	Negative
-------------------------	--	--	--	--	--	----------

Calcium carbonate						
Toxicity/effect	End point	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>2000	mg/kg	Rat	OECD 420 (Acute Oral toxicity - Fixed Dose Procedure)	
Acute toxicity, by dermal route:	LD50	>2000	mg/kg	Rat	OECD 402 (Acute Dermal Toxicity)	
Acute toxicity, by inhalation:	LC50	>3	mg/l /4h	Rat	OECD 403 (Acute Inhalation Toxicity)	
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute Dermal Irritation/Corrosion)	Not irritant
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Not irritant
Respiratory or skin sensitisation:				Mouse	OECD 429 (Skin Sensitisation - Local Lymph Node Assay)	Not sensitizing
Germ cell mutagenicity:					OECD 471 (Bacterial Reverse Mutation Test)	Negative
Germ cell mutagenicity:					OECD 476 (In Vitro Mammalian Cell Gene Mutation Test)	Negative
Germ cell mutagenicity:					OECD 473 (In Vitro Mammalian Chromosome Aberration Test)	Negative
Germ cell mutagenicity:					OECD 471 (Bacterial Reverse Mutation Test)	Negative
Germ cell mutagenicity:					OECD 476 (In Vitro Mammalian Cell Gene Mutation Test)	Negative
Germ cell mutagenicity:					OECD 473 (In Vitro Mammalian Chromosome Aberration Test)	Negative
Carcinogenicity:						No indications of such an effect.
Reproductive toxicity:	NO EL	1000	mg/kg bw/d	Rat	OECD 422 (Combined Repeated Dose Tox. Study with the Reproduction/D. developm. Tox. Screening Test)	
Specific target organ toxicity - single exposure (STOT-SE):						No indications of such an effect.
Specific target organ toxicity - repeated exposure (STOT-RE):						No indications of such an effect.
Aspiration hazard:						No
Symptoms:						blood in urine (haematuria) nausea and vomiting.
Other information:						

Methanol						
Toxicity/effect	End point	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD0	143	mg/kg	Human being		
Acute toxicity, by oral route:	LD50	>5000	mg/kg	Rat	IUCLID Chem. Data Sheet (ESIS)	Not relevant for classification.
Acute toxicity, by oral route:	ATE	300	mg/kg	Human being		Experiences on persons.
Acute toxicity, by dermal route:	LD50	17100	mg/kg	Rabbit		Does not conform with EU classification.
Acute toxicity, by inhalation:	LC50	85	mg/l /4h	Rat		Not relevant for classification.
Skin corrosion/irritation:				Rabbit		Mild irritant
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Mild irritant
Respiratory or skin sensitisation:				Guinea pig	OECD 406 (Skin Sensitisation)	Not sensitizing
Germ cell mutagenicity:					OECD 471 (Bacterial Reverse Mutation Test)	Negative
Symptoms:						abdominal pain, vomiting, headaches, gastrointestinal disturbances, drowsiness, visual disturbances, watering eyes, nausea, mental confusion

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revised on / Version: 17.04.2013 / 0003
 Replaces revision of / Version: 01.07.2013 / 0002
 Valid from: 17.04.2013
 PDF print date: 16.10.2014
 HUECK Hybrid-System-Kleber / hellgrau
 HUECK Hybrid-System-Kleber / dunkelgrau
 Art.: Z91804700.0001 / Z91808800.0001

SECTION 12: Ecological information

Possibly more information on environmental effects, see Section 2.1 (classification).

HUECK Hybrid-System-Kleber / hellgrau
HUECK Hybrid-System-Kleber / dunkelgrau
 Art.: Z91804700.0001 / Z91808800.0001

Toxicity/effect	Endpo int	Ti me	Val ue	Unit	Organism	Test method	Notes
Toxicity to fish:							n.d.a.
Toxicity to daphnia:							n.d.a.
Toxicity to algae:							n.d.a.
Persistence and degradability:							n.d.a.
Bioaccumulative potential:							n.d.a.
Mobility in soil:							n.d.a.
Results of PBT and vPvB assessment							n.d.a.
Other adverse effects:							n.d.a.

trimethoxyvinylsilane

Toxicity/effect	Endpo int	Ti me	Val ue	Unit	Organism	Test method	Notes
Toxicity to fish:	LC50	96 h	>= 100	mg/l	Brachydanio rerio		
Toxicity to fish:	LC50	96 h	191	mg/l	Oncorhynchus mykiss		
Toxicity to fish:	LC50	96 h	191	mg/l	Oncorhynchus mykiss	OECD 203 (Fish, Acute Toxicity Test)	
Toxicity to daphnia:	EC50	48 h	16,87	mg/l	Daphnia magna	Regulation (EC) 440/2008 C.2 (DAPHNIA SP. ACUTE IMMOBILISATION TEST)	
Toxicity to algae:	EC50	72 h	>9,57	mg/l	Scenedesmus subspicatus		
Toxicity to algae:	IC50	72 h	>100	mg/l	Selenastrum capricornutum		
Toxicity to algae:	NOEC/NOEL	72 h	>9,57	mg/l	Scenedesmus subspicatus		88/302/EC
Persistence and degradability:		28 d	51	%		OECD 301 F (Ready Biodegradability - Manometric Respirometry Test)	
Persistence and degradability:		28 d				OECD 301 F (Ready Biodegradability - Manometric Respirometry Test)	Readily biodegradable
Bioaccumulative potential:			-2				product of hydrolysis @20°C
Results of PBT and vPvB assessment							No PBT substance, No vPvB substance
Results of PBT and vPvB assessment							No PBT substance, No vPvB substance
Toxicity to bacteria:	EC50		>2500	mg/l	activated sludge		

3-(trimethoxysilyl)propylamine

Toxicity/effect	Endpo int	Ti me	Val ue	Unit	Organism	Test method	Notes
Toxicity to fish:	LC50		1264	mg/l	Pimephales promelas		
Toxicity to daphnia:	EC50		302	mg/l	Daphnia magna		n.d.a.
Persistence and degradability:							
Toxicity to bacteria:	EC50		3400	mg/l	activated sludge		
Water solubility:							Insoluble

Calcium carbonate

Toxicity/effect	Endpo int	Ti me	Val ue	Unit	Organism	Test method	Notes
Toxicity to fish:	LC50	96 h	>100	mg/l	Oncorhynchus mykiss	OECD 203 (Fish, Acute Toxicity Test)	v/v saturated solution of test material
Toxicity to daphnia:	LC50	48 h	>1	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	v/v saturated solution of test material
Toxicity to algae:	EC50	72 h	>14	mg/l	Desmodesmus subspicatus	OECD 201 (Alga, Growth Inhibition Test)	

Toxicity to algae:	NOEC/NOEL	72 h	14	mg/l	Desmodesmus subspicatus	OECD 201 (Alga, Growth Inhibition Test)	
Persistence and degradability:							Not relevant for inorganic substances.
Bioaccumulative potential:							No
Mobility in soil:							n.a.
Results of PBT and vPvB assessment							No PBT substance, No vPvB substance
Toxicity to bacteria:	EC50	3h	>1000	mg/l	activated sludge	OECD 209 (Activated Sludge, Respiration Inhibition Test (Carbon and Ammonium Oxidation))	
Toxicity to bacteria:	NOEC/NOEL	3h	1000	mg/l	activated sludge	OECD 209 (Activated Sludge, Respiration Inhibition Test (Carbon and Ammonium Oxidation))	
Other organisms:	NOEC/NOEL	14 d	1000	mg/kg dw	Eisenia foetida	OECD 207 (Earthworm, Acute Toxicity Tests)	
Other organisms:	NOEC/NOEL	21 d	1000	mg/kg dw		OECD 208 (Terrestrial Plants, Growth Test)	Glycine max
Other organisms:	NOEC/NOEL	21 d	1000	mg/kg dw		OECD 208 (Terrestrial Plants, Growth Test)	Avena sativa
Other organisms:	NOEC/NOEL	21 d	1000	mg/kg dw		OECD 208 (Terrestrial Plants, Growth Test)	Lycopersicon esculentum
Other organisms:	NOEC/NOEL	21 d	1000	mg/kg dw		OECD 208 (Terrestrial Plants, Growth Test)	Glycine max
Other organisms:	NOEC/NOEL	21 d	1000	mg/kg dw		OECD 208 (Terrestrial Plants, Growth Test)	Avena sativa
Other organisms:	NOEC/NOEL	21 d	1000	mg/kg dw		OECD 208 (Terrestrial Plants, Growth Test)	Lycopersicon esculentum
Other organisms:	NOEC/NOEL	28 d	1000	mg/kg dw		OECD 216 (Soil Microorganisms - Nitrogen Transformation Test)	
Water solubility:			0,0166	g/l		OECD 105 (Water Solubility)	20°C

Methanol

Toxicity/effect	Endpo int	Ti me	Val ue	Unit	Organism	Test method	Notes
Toxicity to fish:	LC50	96 h	15400	mg/l	Lepomis macrochirus		
Toxicity to daphnia:	EC50	48 h	>10000	mg/l	Daphnia magna		
Toxicity to algae:	IC50	72 h	8000	mg/l			
Persistence and degradability:	BOD5/COD		<50	%			
Bioaccumulative potential:	BCF		28400		Chlorella vulgaris		
Other information:	BOD		>60	%			Readily biodegradable
Other information:	DOC		<70	%			

SECTION 13: Disposal considerations

13.1 Waste treatment methods

For the substance / mixture / residual amounts

EC disposal code no.:
 The waste codes are recommendations based on the scheduled use of this product. Owing to the user's specific conditions for use and disposal, other waste codes may be allocated under certain circumstances. (2001/118/EC, 2001/119/EC, 2001/573/EC) 08 04 09 waste adhesives and sealants containing organic solvents or other dangerous substances
 Recommendation:
 Pay attention to local and national official regulations
 E.g. suitable incineration plant.
 E.g. dispose at suitable refuse site.

For contaminated packing material

Pay attention to local and national official regulations
 Empty container completely.
 Uncontaminated packaging can be recycled.
 Dispose of packaging that cannot be cleaned in the same manner as the substance.
 15 01 10 packaging containing residues of or contaminated by dangerous substances

SECTION 14: Transport information

General statements

UN number: n.a.
Transport by road/by rail (ADR/RID)
 UN proper shipping name:
 Transport hazard class(es): n.a.
 Packing group: n.a.
 Classification code: n.a.
 LQ (ADR 2013): n.a.
 LQ (ADR 2009): n.a.
 Environmental hazards: Not applicable
 Tunnel restriction code:

Transport by sea (IMDG-code)
 UN proper shipping name:
 Transport hazard class(es): n.a.
 Packing group: n.a.
 Marine Pollutant: n.a.
 Environmental hazards: Not applicable

Transport by air (IATA)
 UN proper shipping name:
 Transport hazard class(es): n.a.
 Packing group: n.a.
 Environmental hazards: Not applicable

Special precautions for user
 Unless specified otherwise, general measures for safe transport must be followed.
Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code
 Non-dangerous material according to Transport Regulations.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

For classification and labelling see Section 2.
 Observe restrictions:
 Directive 2010/75/EU (VOC): 0 g/l

15.2 Chemical safety assessment
 A chemical safety assessment is not provided for mixtures.

SECTION 16: Other information

These details refer to the product as it is delivered.
 Revised sections: n.a.
 The following phrases represent the posted R phrases / H phrases, Hazard Class and Risk Category Code (GHS/CLP) of the product and the constituents (specified in Section 2 and 3).
 10 Flammable.
 20 Harmful by inhalation.
 38 Irritating to skin.
 41 Risk of serious damage to eyes.
 H226 Flammable liquid and vapour.
 H315 Causes skin irritation.
 H318 Causes serious eye damage.
 H332 Harmful if inhaled.

Flam. Liq. — Flammable liquid
 Acute Tox. — Acute toxicity - inhalation
 Skin Irrit. — Skin irritation
 Eye Dam. — Serious eye damage

Any abbreviations and acronyms used in this document:

- AC Article Categories
- acc., acc. to according, according to
- ACGIH American Conference of Governmental Industrial Hygienists
- ADR Accord européen relatif au transport international des marchandises Dangereuses par Route (= European Agreement concerning the International Carriage of Dangerous Goods by Road)
- AOEL Acceptable Operator Exposure Level
- AOX Adsorbable organic halogen compounds
- approx. approximately
- Art., Art. no. Article number
- ATE Acute Toxicity Estimate according to Regulation (EC) 1272/2008 (CLP)
- BAM Bundesanstalt für Materialforschung und -prüfung (Federal Institute for Materials Research and Testing, Germany)
- BAuA Bundesanstalt für Arbeitsschutz und Arbeitsmedizin (= Federal Institute for Occupational Health and Safety, Germany)
- BCF Bioconcentration factor
- BGV Berufsgenossenschaftliche Vorschrift (= Accident Prevention Regulation)
- BHT Butylhydroxytoluol (= 2,6-Di-*t*-butyl-4-methyl-phenol)
- BMGV Biological monitoring guidance value (EH40, UK)
- BOD Biochemical oxygen demand
- BSEF Bromine Science and Environmental Forum
- bw body weight
- CAS Chemical Abstracts Service
- CEC Coordinating European Council for the Development of Performance Tests for Fuels, Lubricants and Other Fluids
- CESIO Comité Européen des Agents de Surface et de leurs Intermédiaires Organiques
- CIPAC Collaborative International Pesticides Analytical Council
- CLP Classification, Labelling and Packaging (REGULATION (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures)
- CMR carcinogenic, mutagenic, reproductive toxic
- COD Chemical oxygen demand
- CTFA Cosmetic, Toiletary, and Fragrance Association
- DMEL Derived Minimum Effect Level
- DNEL Derived No Effect Level
- DOC Dissolved organic carbon
- DT50 Dwell Time - 50% reduction of start concentration
- DVS Deutscher Verband für Schweißen und verwandte Verfahren e.V. (= German Association for Welding and Allied Processes)
- dw dry weight
- e.g. for example (abbreviation of Latin 'exempli gratia'), for instance
- EC European Community
- ECHA European Chemicals Agency
- EEA European Economic Area
- EEC European Economic Community
- EINECS European Inventory of Existing Commercial Chemical Substances
- ELINCS European List of Notified Chemical Substances
- EN European Norms
- EPA United States Environmental Protection Agency (United States of America)
- ERC Environmental Release Categories
- ES Exposure scenario
- etc. et cetera
- EU European Union
- EWV European Waste Catalogue
- Fax. Fax number

- gen. general
- GHS Globally Harmonized System of Classification and Labelling of Chemicals
- GWP Global warming potential
- HET-CAM Hen's Egg Test - Chorionallantoic Membrane
- HGWP Halocarbon Global Warming Potential
- IARC International Agency for Research on Cancer
- IATA International Air Transport Association
- IBC Intermediate Bulk Container
- IBC (Code) International Bulk Chemical (Code)
- IC Inhibitory concentration
- IMDG-code International Maritime Code for Dangerous Goods
- incl. including, inclusive
- IUCLID International Uniform Chemical Information Database
- LC lethal concentration
- LC50 lethal concentration 50 percent kill
- LCLo lowest published lethal concentration
- LD Lethal Dose of a chemical
- LD50 Lethal Dose, 50% kill
- LDLo Lethal Dose Low
- LOAEL Lowest Observed Adverse Effect Level
- LOEC Lowest Observed Effect Concentration
- LOEL Lowest Observed Effect Level
- LQ Limited Quantities
- MARPOL International Convention for the Prevention of Marine Pollution from Ships
- n.a. not applicable
- n.av. not available
- n.c. not checked
- n.d.a. no data available
- NIOSH National Institute of Occupational Safety and Health (United States of America)
- NOAEC No Observed Adverse Effective Concentration
- NOAEL No Observed Adverse Effect Level
- NOEC No Observed Effect Concentration
- NOEL No Observed Effect Level
- ODP Ozone Depletion Potential
- OECD Organisation for Economic Co-operation and Development
- org. organic
- PAH polycyclic aromatic hydrocarbon
- PBT persistent, bioaccumulative and toxic
- PC Chemical product category
- PE Polyethylene
- PNEC Predicted No Effect Concentration
- POCP Photochemical ozone creation potential
- ppm parts per million
- PROC Process category
- PTFE Polytetrafluorethylene
- REACH Registration, Evaluation, Authorisation and Restriction of Chemicals (REGULATION (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals)
- REACH-IT List-No. 9xx-xxx-x No. is automatically assigned, e.g. to pre-registrations without a CAS No. or other numerical identifier. List Numbers do not have any legal significance, rather they are purely technical identifiers for processing a submission via REACH-IT.
- RID Règlement concernant le transport International ferroviaire de marchandises Dangereuses (= Regulation concerning the International Carriage of Dangerous Goods by Rail)
- SADT Self-Accelerating Decomposition Temperature
- SAR Structure Activity Relationship
- SU Sector of use
- SVHC Substances of Very High Concern
- Tel. Telephone
- ThOD Theoretical oxygen demand
- TOC Total organic carbon
- TRGS Technische Regeln für Gefahrstoffe (=Technical Regulations for Hazardous Substances)
- UN RTDG United Nations Recommendations on the Transport of Dangerous Goods
- VbF Verordnung über brennbare Flüssigkeiten (= Regulation for flammable liquids (Austria))
- VOC Volatile organic compounds
- vPvB very persistent and very bioaccumulative
- WEL-TWA, WEL-STEL WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period), WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period) (EH40, UK).
- WHO World Health Organization
- wt wet weight

The statements made here should describe the product with regard to the necessary safety precautions - they are not meant to guarantee definite characteristics - but they are based on our present up-to-date knowledge. No responsibility.

These statements were made by:
Chemical Check GmbH, Chemical Check Platz 1-7, D-32839 Steinheim, Tel.: +49 5233 94 17 0, Fax: +49 5233 94 17 90

© by Chemical Check GmbH Gefahrstoffberatung. The copying or changing of this document is forbidden except with consent of the Chemical Check GmbH Gefahrstoffberatung.